

Contract Line No.	Item Description	Supplier Part No.	Unit of Measure	Estimated Usage	Unit Price	Extended Total
1	Delta DBT 2025: Decharacterized liquid oxygen. Liquid used in oxygen scavenging of boiler water 30 gallon drum	DBT 2025 - 30	Drum	1		
2	Delta DBT-2025: Decharacterized liquid oxygen. Liquid used in oxygen scavenging of boiler water 55 gallon drum	DBT 2025 - 55	Drum	3		
3	Delta DBT 2040: Oxygen scavenger, catalyzed liquid sodium bi-sulfite used in oxygen scavenging of boiler water 15 gallon drum	DBT 2040 - 15	Drum	1		
4	Delta DBT 2040: Oxygen scavenger, catalyzed liquid sodium bi-sulfite used in oxygen scavenging of boiler water 30 gallon drum	DBT 2040 - 30	Drum	1		
5	Delta DBT 2040: Oxygen scavenger, catalyzed liquid sodium bi-sulfite used in oxygen scavenging of boiler water 55 gallon drum	DBT 2040 - 55	Drum	1		
6	Delta DBT 4020: Boiler water compound, chelant/polymer blend of boiler water treatment 30 gallon drum	DBT 4020 - 30	Drum	1		
7	Delta DBT 4020: Boiler water compound, chelant/polymer blend of boiler water treatment 55 gallon drum	DBT 4020 - 55	Drum	1		
8	Delta DBT 4800-L: Boiler water compound, organic boiler water internal treatment 30 gallon drum	DBT 4800-L - 30	Drum	1		
9	Delta DBT 4800-L: Boiler water compound, organic boiler water internal treatment 55 gallon drum	DBT 4800-L - 55	Drum	1		
10	Delta DBT 6315: Boiler water compound, blend of cyclohexylamine/morpholine steam treatment 30 gallon drum	DBT 6315 - 30	Drum	1		
11	Delta DBT 6315: Boiler water compound, blend of cyclohexylamine/morpholine steam treatment 55 gallon drum	DBT 6315 - 55	Drum	4		
12	Delta DCT 1111-L: Corrosion/scale/sludge inhibitor program for open recirculating cooling water system molybdate based 30 gallon drum	DCT 1111L - 30	Drum	1		
13	Delta DCT 1111-L: Corrosion/scale/sludge inhibitor program for open recirculating cooling water system molybdate based 55 gallon drum	DCT 1111L - 55	Drum	23		
14	Delta DCT 1111-L: Corrosion/scale/sludge inhibitor program for open recirculating cooling water system molybdate based 250 gallon minimum bulk delivery 9.46 pounds per gallon	DCT 1111L - B	Pound	1		
15	Delta DCT 3000A: Algae/microbe control, slow release pelletized bromine agent for control of bacterial fungi and algae in open tower system, treating industrial recirculating cooling water, ornamental fountains and air conditioner condensate 50 pounds per pail	DCT 3000A	Each	18		
16	Delta DCT-3005-P: Algae/microbe control. Biological control agent for open recirculating cooling tower water system 5 gallon pail	DCT-3005P - 5	Each	1		
17	Delta DCT-3005-P: Algae/microbe control. Biological control agent for open recirculating cooling tower water system 30 gallon drum	DCT 3005P - 30	Drum	1		
18	Delta DCT-3005-P: Algae/microbe control. Biological control agent for open recirculating cooling tower water system 55 gallon drum	DCT 3005P - 55	Drum	8		
19	Delta DCT 3015: Algae/microbe control, biological control agent for open recirculating cooling tower water systems 15 gallon drum	DCT 3015 - 15	Drum	1		
20	Delta DCT 3015: Algae/microbe control, biological control agent for open recirculating cooling tower water systems 30 gallon drum	DCT 3015 - 30	Drum	1		
21	Delta DCT 3015: Algae/microbe control, biological control agent for open recirculating cooling tower water systems 55 gallon drum	DCT 3015 - 55	Drum	1		
22	Delta DCT 5250: Corrosion/scale/sludge inhibitor, closed loop treatment for chilled/hot water system, nitrite based 5 gallon pail	DCT 5250 - 5	Each	1		

23	Delta DCT 5250: Corrosion/scale/sludge inhibitor, closed loop treatment for chilled/hot water system, nitrite based 30 gallon drum	DCT 5250 - 30	Drum	8		
24	Delta DCT 5250: Corrosion/scale/sludge inhibitor, closed loop treatment for chilled/hot water system, nitrite based 55 gallon drum	DCT 5250 - 55	Drum	15		
25	Delta DWT 6035: Corrosion/scale/sludge inhibitor/iron sequestant for potable water (nsf/ansi/can standard 60 approved - max use 29 mg/L) 330 gallon minimum bulk delivery One gallon equals 14.54 pounds	DWT 6035 - B	Pound	1		
26	Delta DWT 7022: Corrosion/scale/sludge inhibitor, zinc orthophosphate corrosion inhibitor for potable systems (NSF/ANSI/CAN standard 60 approved - max use 25 mg/L.) 55 gallon drum	DWT 7022 - 55	Drum	1		
27	Delta DWT 7022: Corrosion/Scale/Sludge Inhibitor, Zinc Orthophosphate Corrosion Inhibitor for Potable Systems (NSF/ANSI/CAN standard 60 approved - max use 25 mg/L.) 330 gallon minimum bulk delivery One gallon equals 11 pounds	DWT 7022 - B	Pound	1		
28	Delta DWT 7055: Corrosion/scale/sludge inhibitor, zinc orthophosphate corrosion inhibitor for potable systems (NSF/ANSI/CAN standard 60 approved - max use 18 mg/L) 55 gallon drum	DWT 7055 - 55	Drum	1		
29	Delta DWT 7055: Corrosion/scale/sludge inhibitor, zinc orthophosphate corrosion inhibitor for potable systems (NSF/ANSI/CAN standard 60 approved - max use 18 mg/L) 330 gallon minimum bulk delivery One gallon equals 13.35 pounds	DWT 7055 - B	Pound	1		
30	Delta DWT 7723: Liquid Orthopolyphosphate blend corrosion inhibitor (NSF/ANSI/CAN standard 60 approved - max use 29 mg/L). 330 gallon minimum bulk delivery One gallon equals eleven and thirty-five hundredths (11.35) pounds	DWT 7723 - B	Pound	1		
31	Delta DWT 7723: Liquid Orthopolyphosphate blend corrosion inhibitor (NSF/ANSI/CAN standard 60 approved - max use 29 mg/L) 620 pounds per drum	DWT 7723 - 55	Drum	1		
32	Delta DWT 8020: Cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water systems (NSF/ANSI/CAN standard 60 approved - max use 50 mg/L) 55 gallon drum	DWT 8020 - 55	Drum	1		
33	Delta DWT 8020: Cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water systems (NSF/ANSI/CAN standard 60 approved - max use 50 mg/L) 2,300 pounds per tote bulk delivery One gallon equals 9.18 pounds per gallon	DWT 8020 - B	Pound	55200		
34	Delta DWT 8050: Cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water systems 55 gallon drum	DWT 8050 - 55	Drum	1		
35	Delta DWT 8050: Cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water systems 2,300 pounds per tote bulk delivery One gallon equals 8.36 pounds per gallon	DWT 8050 - B	Pound	4940		
36	Delta DWT 8408: Liquid blend of cationic polymer used in emulsion for potable water and waste water systems, bulk 1,500 gallon minimum One gallon equals 8.76 pounds	DWT 8408 - T	Pound	55440		
37	Delta- 24: Hydrofluosilic acid 23% - 25%. Fluoride based potable water treatment 275 gallon minimum (NSF/ANSI/CAN standard 60 approved - max use 5 mg/L) One gallon equals 10.15 pounds per gallon	Delta 24	Pound	13087		
38	Delta 8548SH: Cationic water-soluble polymer powder used as processing aid to achieve clarification in waste water system dewatering, bulk One pallet minimum, 40 X 55 pound bags per pallet	Delta 8548SH	Pound	11000		

39	DeltaChlor: 12.5% Sodium hypochlorite potable water disinfectant/cooling tower disinfectant (NSF/ANSI/CAN standard 60 approved - max use 49 mg/L) 55 gallon drum	DeltaChlor - 55	Drum	21		
40	DeltaChlor: 12.5% Sodium hypochlorite potable water disinfectant/cooling tower disinfectant (NSF/ANSI/CAN standard 60 approved - max use 49 mg/L) 330 gallon minimum, bulk delivery	DeltaChlor - B	Gallon	189870		
41	Delta DCT 1111-T: Multi purpose cooling water corrosion/sludge inhibitor with tracer for enhanced monitoring and control 30 gallon drum	DCT1111T-30	Drum	1		
42	Delta DCT 1111-T: Multi purpose cooling water corrosion/sludge inhibitor with tracer for enhanced monitoring and control 55 gallon drum	DCT1111T-55	Drum	15		
43	DWT 8640: High molecular cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water system 55 gallon drum	DWT 8640 - 55	Drum	1		
44	DWT 8640: High molecular cationic polymer flocculant treatment, liquid blend of cationic polymers used for clarification in potable water and waste water system 2,300 pounds per tote, bulk delivery One gallon equals 9.18 pounds per gallon	DWT 8640 - B	Pound	780		